



BW TYPE



CW TYPE



Dimension:mm

N o. Of Teeth	Pitch Dia. Dp	Outside Dia. Do	B Type / BW Type					Duplex B Type / Duplex BW Type						
			Bore:d		Hub		Approx. WT.(kg)	Material	Bore:d		Hub		Approx. WT.(kg)	Material
			Min.	Max.	Dh	L			Min.	Max.	Dh	L		
11	202.85	229	43	85	140	75	12.5							
12	220.81	248	48	95	150	75	14.6							
13	238.81	266	58	105	170	80	17.8							
14	256.83	285	58	115	180	80	20.9							
15	274.87	303	58	115	180	80	22.8							
16	292.94	322	58	115	180	80	24.9							
17	311.01	340	58	115	180	80	27.1							
18	329.11	358	58	115	180	80	30.1							
19	347.21	377						68	120	190	85	33.6		
20	365.33	395						68	120	190	85	37.2		
21	383.45	413						68	120	190	85	39.2	SS41	
22	401.57	432						68	120	190	85	41.7	(CW TYPE)	
23	419.71	450						68	120	190	85	45.1		
24	437.84	468						68	120	190	85	48.2		
25	455.99	487						68	120	190	85	52.2		
28	510.43	541						68	125	200	90	64.3		
30	546.74	578						78	135	215	110	78.7		
35	637.56	669						78	135	215	110	101.0		
40	728.41	760						78	135	215	110	126.0		
45	819.28	852						78	135	230	125	162.0		
50	910.17	943						78	135	230	125	193.0		

NOTE:1.B-type &C-type solid sprocket made by S35C are available