





A TYPE

B TYPE

B TYPE

BW TYPE

DUPLEX B TYPE

DUPLEX BW TYPE


Dimension:mm

No. Of Teeth	Pitch Dia. Dp	Outside Dia. Do	A Type		Material	B Type / BW Type					Material	Duplex Btype / Duplex BW Type					Material		
			Bore: d	Approx. WT.(kg)		Bore:d		Hub		Approx. WT.(kg)		Bore:d	Hub	Approx. WT.(kg)	Bore:d	Hub		Approx. WT.(kg)	
						Min.	Max.	Dh	L										Min.
8	41.48	47.0	9	0.09	SS41	9	15.9	28.6	25.4	0.19	*								
9	46.41	52.6	10	0.10		10	19	34	25	0.20	*								
10	51.38	57.5	10	0.11		10	22	40	25	0.27	*	14	22	35	40	0.38			
11	56.35	63.0	10	0.15		13	24	46	25	0.33	*	14	24	40	40	0.50			
12	61.34	68.0	12	0.18		13	30	51	25	0.41	*	14	26	42	40	0.60			
13	66.34	73.0	13	0.18		13	30	51	25	0.46	*	14	30	49	40	0.73			
14	71.34	78.0	13	0.20		13	32	52	25	0.52		14	32	54	40	0.87			
15	76.35	83.0	13	0.26		13	36	57	25	0.62		14	35	59	40	1.00			
16	81.37	88.0	13	0.30		13	40	62	25	0.72		14	38	64	45	1.30			
17	86.39	93.0	13	0.35		13	42	67	25	0.83		14	40	68	45	1.50			
18	91.42	98.3	13	0.40		13	48	72	28	1.00		14	45	74	45	1.70			
19	96.45	103.3	13	0.44		13	48	73	28	1.10		14	48	79	45	2.00			
20	101.48	108.4	14	0.50		14	48	73	28	1.20		18	50	84	45	2.20			
21	106.51	113.4	14	0.54		14	48	73	28	1.20		18	54	89	45	2.50			
22	111.56	118.0	16	0.59		16	48	73	28	1.30		18	65	94	50	2.90			
23	116.58	123.4	16	0.65		16	48	73	28	1.30		18	65	99	50	3.30			
24	121.62	128.3	16	0.70		16	48	73	28	1.45	S35C (B TYPE)	18	65	105	50	3.60	S35C (DUPLEX B TYPE)		
25	126.66	134.0	16	0.80		16	48	73	28	1.50		18	65	105	50	4.00			
26	131.70	139.0	16	0.85		16	48	73	28	1.50		18	65	105	50	4.40			
27	136.74	144.0	16	0.90		16	48	73	28	1.50		18	65	105	50	4.80			
28	141.79	148.7	16	1.00		16	48	73	28	1.60		18	70	110	50	4.90			
29	146.83	153.8	16	1.10		16	48	73	28	1.70		18	70	110	50	4.95			
30	151.87	158.8	16	1.15		16	48	73	28	1.80		18	80	120	50	5.00			
31	156.92	163.9	16	1.20		16	48	73	28	1.80		23	80	120	50	5.20			
32	161.96	168.9	16	1.26		16	48	73	28	1.90		23	80	120	50	5.30			
33	167.01	174.5	16	1.35		16	48	73	28	2.00		23	80	120	50	5.40			
34	172.05	179.0	16	1.45		16	48	73	28	2.10	23	80	120	50	5.60				
35	177.10	184.1	16	1.55		16	48	73	28	2.20	23	80	117	50	5.80				
36	182.14	189.1	19	1.67		19	52	83	35	2.70	23	80	117	50	5.90				
37	187.19	194.2	19	1.80		19	52	83	35	2.80									
38	192.24	199.2	19	1.85	19	52	83	35	2.90		23	80	117	50	5.90				
39	197.29	204.2	19	2.00	19	52	83	35	3.00										
40	202.33	209.3	19	2.05	19	52	83	35	3.10		23	80	117	56	6.20				
41	207.38	214.8	19	2.12	19	52	83	35	3.20										
42	212.43	219.9	19	2.30	19	52	83	35	3.30		23	65	98	56	7.10				
43	217.48	224.9	19	2.43	19	52	83	35	3.40										
44	222.53	230.0	19	2.60	19	52	83	35	3.50										
45	227.58	235.0	19	2.60	19	52	83	35	3.60	SS41 (BW TYPE)	23	65	98	56	7.30				
46	232.63	240.1	19	2.70	19	52	83	35	4.00		23	65	98	56	8.20				
48	242.73	250.2	19	3.00	19	52	83	35	4.00		23	65	98	56	9.00				
50	252.83	260.3	19	3.30	19	52	83	35	4.20		23	65	98	56	9.90				
54	273.02	280.5	19	3.90	19	52	83	35	4.80		23	65	98	63	11.70				
60	303.33	310.8	19	4.80	19	52	83	35	5.60		23	65	98	63	13.80				
65	328.58	336.5	19	5.80	19	60	93	40	6.90		23	65	98	63	14.60				
70	353.84	361.8	20	6.35	20	60	93	40	7.70		23	65	98	63	20.30				
75	379.10	387.1	20	7.00	20	60	93	40	8.60		23	65	108	63	22.22				
80	404.36	412.3	20	8.45	20	60	93	40	10.10										
85	429.62	437.6	20	9.00	20	63	93	40	11.60										
90	454.80	462.8	20	9.50	20	63	93	40	13.10										

NOTE:1. Sprocket marked with an asterisk (*) has a groove at the external circumference of hub. Groove diameters (Dg) are :8T=36.00mm, 9T=27.00mm, 10T=32.00mm, 11T=37.00mm, 12T=42.00mm, 13T=47.00mm.

2. 8-13 teeth of duplex B type sprockets have a groove at the external circumference of hub. Refer to single B type sprocket about width and position of the groove.

3. B-type solid sprockets over 35 teeth made by S35C are available.